

XDJ-AZ-N

All-In-One DJ System Système DJ tout-en-un All-In-One-DJ-System Sistema DJ tutto in uno Alles-in-één-DJ-System Sistema DJ Todo en uno Sistema para DJ Tudo-Em-Um DJ система все-в-одном

Precautions for Use Précautions à l'utilisation Hinweise für den Gebrauch Precauzioni Voorzorgsmaatregelen Precauciones al usar Precauções Правила предосторожности при эксплуатации

alphatheta.com/support/ alphatheta.com/support/France/ alphatheta.com/support/Germany/ alphatheta.com/support/Italy/ alphatheta.com/support/Netherlands/ alphatheta.com/support/Spain/ alphatheta.com/support/Portugal/ alphatheta.com/support/Russia/ rekordbox.com

For FAQ and other support information for this product, visit the websites above.

Pour consulter la FAQ et d'autres informations d'assistance concernant ce produit, visitez les sites Web ci-dessus.

Häufig gestellte Fragen und andere Supportinformationen zu diesem Produkt finden Sie auf den oben genannten Websites.

Per la sezione FAQ e altre informazioni di supporto per questo prodotto, visitate i siti web indicati sopra.

Bezoek de bovenstaande websites voor vaak gestelde vragen en andere informatie over ondersteuning voor dit product.

Para consultar las preguntas más frecuentes y otras informaciones de asistencia para este producto, visite los sitios web indicados anteriormente.

Para ver as perguntas frequentes e obter outras informações de assistência relativa a este produto, consulte os sites indicados acima.

Справка задаваемых вопросов и другую информацию о поддержке данного изделия см. на перечисленных выше сайтах.

For FAQ and other support information for this product, visit the websites above.

Pour consulter la FAQ et d'autres informations d'assistance concernant ce produit, visitez les sites Web ci-dessus.

Häufig gestellte Fragen und andere Supportinformationen zu diesem Produkt finden Sie auf den oben genannten Websites.

Per la sezione FAQ e altre informazioni di supporto per questo prodotto, visitate i siti web indicati sopra.

Bezoek de bovenstaande websites voor vaak gestelde vragen en andere informatie over ondersteuning voor dit product.

Para consultar las preguntas más frecuentes y otras informaciones de asistencia para este producto, visite los sitios web indicados anteriormente.

Para ver as perguntas frequentes e obter outras informações de assistência relativa a este produto, consulte os sites indicados acima.

Справка задаваемых вопросов и другую информацию о поддержке данного изделия см. на перечисленных выше сайтах.

IMPORTANT SAFETY INSTRUCTIONS

- Read these instructions.
- Keep these instructions.
- Read all warnings.
- Follow all instructions from the manufacturer, or sold with the apparatus. When a cart is used, use caution when moving the cart/apparatus combination to avoid injury from tip-over.
- Do not clean with dry cloth.
- Do not block any ventilation openings. Install in accordance with the manufacturer's instructions.
- Do not install near any heat sources such as radiators, heat registers, stoves, or other apparatus (including amplifiers) that produce heat.
- Do not defeat the safety purpose of the polarized or grounding-type plug. A polarized plug has two blades with one wider than the other. A grounding type plug has two blades and a third grounding prong. The wide blade or the third prong are provided for your safety. If the provided plug does not fit into your outlet, consult an electrician for replacement of the obsolete outlet.
- Protect the power cord from being walked on or pinched particularly at plugs, convenience receptacles, and the point where they exit from the apparatus.

- Only use attachments/accessories specified by the manufacturer.
- Use only with the cart, stand, tripod, bracket, or table specified by the manufacturer, or sold with the apparatus. When a cart is used, use caution when moving the cart/apparatus combination to avoid injury from tip-over.
- Unplug this apparatus during lightning storms or when unused for long periods of time.
- Refer all servicing to qualified service personnel. Servicing is required when the apparatus has been damaged in any way, such as power-supply cord or plug is damaged, liquid has been spilled or objects have fallen into the apparatus, the apparatus has been exposed to rain or moisture, does not operate normally, or has been dropped.

FEDERAL COMMUNICATIONS COMMISSION DECLARATION OF CONFORMITY
This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Product Name: ALL-IN-ONE DJ SYSTEM
Model Number: XDJ-AZ-N
Responsible Party Name: AlphaTheta Music Americas, Inc. OPERATIONS DIVISION
Address: 2050 W. 190th Street, Suite 109, Torrance, CA 90504, U.S.A.
Phone: 1-424-488-0480
URL: alphatheta.com

NOTE:
This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and it may interfere with radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:
— Reorient or relocate the receiving antenna.
— Increase the separation between the equipment and receiver.
— Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
— Consult the dealer or an experienced radio/TV technician for help.

Information to User
Alterations or modifications carried out without appropriate authorization may invalidate the user's right to obtain the equipment.

CAUTION
This product satisfies FCC regulations when shielded cables and connectors are used to connect the unit to other equipment. To prevent electromagnetic interference with electric appliances such as radios and televisions, use shielded cables and connectors for connections.

This transmitter must not be co-located or operated in conjunction with any other antenna or transmitter.

5.15 GHz - 5.25 GHz band is restricted to indoor operations only.

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment and meets the FCC radio frequency (RF) Exposure Guidelines. This equipment should be installed and operated keeping the radiator at least 20 cm or more away from person's body.

Product Name: ALL-IN-ONE DJ SYSTEM
Model Number: XDJ-AZ-N
Responsible Party Name: AlphaTheta Music Americas, Inc. OPERATIONS DIVISION
Address: 2050 W. 190th Street, Suite 109, Torrance, CA 90504, U.S.A.
Phone: 1-424-488-0480
URL: alphatheta.com

NOTE:
This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and it may interfere with radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:
— Reorient or relocate the receiving antenna.
— Increase the separation between the equipment and receiver.
— Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
— Consult the dealer or an experienced radio/TV technician for help.

Information to User
Alterations or modifications carried out without appropriate authorization may invalidate the user's right to obtain the equipment.

CAUTION
This product satisfies FCC regulations when shielded cables and connectors are used to connect the unit to other equipment. To prevent electromagnetic interference with electric appliances such as radios and televisions, use shielded cables and connectors for connections.

This transmitter must not be co-located or operated in conjunction with any other antenna or transmitter.

5.15 GHz - 5.25 GHz band is restricted to indoor operations only.

CAUTION
TO PREVENT THE RISK OF ELECTRIC SHOCK, DO NOT REMOVE COVER (OR BACK). NO USER-SERVICEABLE PARTS INSIDE. REFER SERVICING TO QUALIFIED SERVICE PERSONNEL.

WARNING
The equipment is not waterproof. To prevent a fire or shock hazard, do not place any container filled with liquid near this equipment (such as a vase or flower pot) or expose it to dripping, spraying, rain or moisture.

WARNING
The product is equipped with a three-wire grounding (earthed) plug - a plug that has a third grounding prong. This plug only fits a grounding type power outlet. If you are unable to insert the plug into the power outlet to replace the cord, please contact your dealer with a properly grounded one. Do not defeat the safety purpose of the grounding plug.

WARNING
To prevent a fire hazard, do not place any naked flame sources (such as a lighted candle) on the equipment.

Operating Environment
Operating environment temperature and humidity:
+5 °C to +35 °C (+41 °F to +95 °F); less than 85 %RH (cooling vents not blocked)
Do not install this unit in a poorly ventilated area, or in locations exposed to high humidity or direct sunlight (or strong artificial light).

VENTILATION CAUTION
When installing this make sure to leave space around the unit for ventilation to improve heat radiation (at least 5 cm at rear, and 5 cm at each side).

CAUTION
The "O" switch on this unit will not completely shut off all power from the AC outlet. Since the power cord serves as the main disconnect device for the unit, you will need to unplug it from the AC outlet to shut down all power. Therefore, make sure the unit has been installed so that the power cord can be easily unplugged from the AC outlet in case of an accident. To avoid fire hazard, the power cord should also be unplugged from the AC outlet when left unused for a long period of time (for example, when on vacation).

The graphical symbol ~ placed on the product means alternating current. The graphical symbol ~ placed on the product means direct current. The graphical symbol ~ placed on the product means Class II equipment.

CAUTION
This product is evaluated in moderate and tropical climate condition.

[for a service technician]
CAUTION
Since the fuse may be in the neutral of the mains supply, disconnect the mains to de-energize the phase conductors.

WARNING
Store small parts out of the reach of children and infants. If accidentally swallowed, contact a doctor immediately.

POWER-CORD CAUTION
Handle the power cord by the plug. Do not pull out the plug by tugging the cord and never touch the power when your hands are wet as this could cause a short circuit or electric shock. Do not place the power cord under furniture, or in a hallway or pinch the cord. Never make a knot in the cord or tie it with other cords. The power cords should be routed such that they are not likely to be stepped on. A damaged power cord can cause a fire or give you an electrical shock. Check the power cord once in a while. When you find it damaged, ask your nearest service center or your dealer for a replacement.

O switch
Turns the unit on and off.

- This unit should not be used by persons who have heart pacemakers installed, since adverse effects could occur.
- Do not use this unit in hospitals or clinics, or near medical equipment.
- Do not use inside airplanes or in the vicinity of automatic doors to avoid danger of causing malfunctions.

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

CAUTION
TO PREVENT THE RISK OF ELECTRIC SHOCK, DO NOT REMOVE COVER (OR BACK). NO USER-SERVICEABLE PARTS INSIDE. REFER SERVICING TO QUALIFIED SERVICE PERSONNEL.

WARNING
The equipment is not waterproof. To prevent a fire or shock hazard, do not place any container filled with liquid near this equipment (such as a vase or flower pot) or expose it to dripping, spraying, rain or moisture.

WARNING
The product is equipped with a three-wire grounding (earthed) plug - a plug that has a third grounding prong. This plug only fits a grounding type power outlet. If you are unable to insert the plug into the power outlet to replace the cord, please contact your dealer with a properly grounded one. Do not defeat the safety purpose of the grounding plug.

WARNING
To prevent a fire hazard, do not place any naked flame sources (such as a lighted candle) on the equipment.

Operating Environment
Operating environment temperature and humidity:
+5 °C to +35 °C (+41 °F to +95 °F); less than 85 %RH (cooling vents not blocked)
Do not install this unit in a poorly ventilated area, or in locations exposed to high humidity or direct sunlight (or strong artificial light).

VENTILATION CAUTION
When installing this make sure to leave space around the unit for ventilation to improve heat radiation (at least 5 cm at rear, and 5 cm at each side).

CAUTION
The "O" switch on this unit will not completely shut off all power from the AC outlet. Since the power cord serves as the main disconnect device for the unit, you will need to unplug it from the AC outlet to shut down all power. Therefore, make sure the unit has been installed so that the power cord can be easily unplugged from the AC outlet in case of an accident. To avoid fire hazard, the power cord should also be unplugged from the AC outlet when left unused for a long period of time (for example, when on vacation).

The graphical symbol ~ placed on the product means alternating current. The graphical symbol ~ placed on the product means direct current. The graphical symbol ~ placed on the product means Class II equipment.

CAUTION
This product is evaluated in moderate and tropical climate condition.

[for a service technician]
CAUTION
Since the fuse may be in the neutral of the mains supply, disconnect the mains to de-energize the phase conductors.

WARNING
Store small parts out of the reach of children and infants. If accidentally swallowed, contact a doctor immediately.

POWER-CORD CAUTION
Handle the power cord by the plug. Do not pull out the plug by tugging the cord and never touch the power when your hands are wet as this could cause a short circuit or electric shock. Do not place the power cord under furniture, or in a hallway or pinch the cord. Never make a knot in the cord or tie it with other cords. The power cords should be routed such that they are not likely to be stepped on. A damaged power cord can cause a fire or give you an electrical shock. Check the power cord once in a while. When you find it damaged, ask your nearest service center or your dealer for a replacement.

O switch
Turns the unit on and off.

- This unit should not be used by persons who have heart pacemakers installed, since adverse effects could occur.
- Do not use this unit in hospitals or clinics, or near medical equipment.
- Do not use inside airplanes or in the vicinity of automatic doors to avoid danger of causing malfunctions.

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

Standard input level/input impedance
LINE PHONO MIC
Standard output level/Load impedance/Output impedance
MASTER 1 MASTER 2
RCA output terminals
RCA pin jacks
MIC input terminals
MIC input terminals
MASTER 1 output terminal
MASTER 2 output terminal
RCA pin jacks
BOOTH output terminal
PHONES output terminal
1/4" stereo jack
3.5 mm stereo mini jack

CAUTION
TO PREVENT THE RISK OF ELECTRIC SHOCK, DO NOT REMOVE COVER (OR BACK). NO USER-SERVICEABLE PARTS INSIDE. REFER SERVICING TO QUALIFIED SERVICE PERSONNEL.

WARNING
The equipment is not waterproof. To prevent a fire or shock hazard, do not place any container filled with liquid near this equipment (such as a vase or flower pot) or expose it to dripping, spraying, rain or moisture.

WARNING
The product is equipped with a three-wire grounding (earthed) plug - a plug that has a third grounding prong. This plug only fits a grounding type power outlet. If you are unable to insert the plug into the power outlet to replace the cord, please contact your dealer with a properly grounded one. Do not defeat the safety purpose of the grounding plug.

WARNING
To prevent a fire hazard, do not place any naked flame sources (such as a lighted candle) on the equipment.

Operating Environment
Operating environment temperature and humidity:
+5 °C to +35 °C (+41 °F to +95 °F); less than 85 %RH (cooling vents not blocked)
Do not install this unit in a poorly ventilated area, or in locations exposed to high humidity or direct sunlight (or strong artificial light).

VENTILATION CAUTION
When installing this make sure to leave space around the unit for ventilation to improve heat radiation (at least 5 cm at rear, and 5 cm at each side).

CAUTION
The "O" switch on this unit will not

